

FFT-WZIC40H130

Image Sensor: | 1.3MP CMOS Image Sensor

Signal System: | PAL | NTSC

Effective Pixels: | 1280(H) × 960(V)

Min. Illumination: | 0.1 Lux @ (F1.2, AGC ON)
0.3 Lux @ (F2.3, AGC ON)

Shutter Time: | 1/25(1/30) s to 1/10,000 s

Lens: | 2.8-12 mm @ F1.4, Angle of view: 35.1°- 114.5°

Lens Mount: | M12

Adjustment Range: | Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°

Day& Night: | IR cut filter with auto switch

Video Frame Rate: | PAL: 960P@25fp
NTSC: 960P@30fps

HD Video Output: | AHD | TVI | CVI | CVBS Output Optional

Synchronization: | Internal Synchronization

S/N Ratio: | More than 62 dB

Up the Coax: | Support

Operating Conditions: | -20 °C - 60 °C (-20 °F - 140 °F)
Humidity 90% or less (non-condensing)

Power Supply: | 12 VDC±15%

Power Consumption: | Max. 4W

IR Range: | Up to 40m

Dimension: | 228mm x 97mm x 82mm

Weight: | 1700g
