

# FT-A200WFIK40

## Camera

---

Image Sensor: | 2MP Progressive Scan CMOS C

---

Signal System: | PAL/NTSC

---

Lens: | CS 12mm lens (CS 6mm/8mm/16mm Optional)

---

Lens Mount: | M12

---

Day& Night: | IR cut filter with auto switch

---

Digital noise reduction: | 3D DNR

---

## Compression Standard

---

Video Compression: | H.265/MJPEG

---

Video bit rate | 32Kbps~8Mbps

---

Triple Streams: | No

---

## Image

---

Max. Image Resolution: | 1920x1080

---

Frame Rate: | 50 Hz: 25 fps (1920 x 1080)  
60 Hz: 30 fps (1920 x 1080)

---

## Network

---

Protocols: | Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception

---

Protocols: | TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP, NTP,UPnP,SMTP,IPv6,

---

General Function: | Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering

---

System Compatibility: | ONVIF (Profile S, Profile G),ISAPI

---

## General

---

Operating Conditions: | -30 °C ~ 60 °C (-22 °F ~ 140 °F)  
Humidity 95% or less (non-condensing)

---

Power Supply: | 12 VDC ± 25%

---

Weather Proof: | IP66

---

IR Range: | Up to 40m

---

Dimensions: | 212x93x110mm

---

Weight: | 1500g

---