

# FT-A400WZIT40A

## Camera

Image Sensor: | 4MP Progressive Scan CMOS C

Signal System: | PAL/NTSC

Lens: | 4.0MP **2.8-12mm** Auto Focus Lens

Lens Mount: | M12

Day& Night: | IR cut filter with auto switch

Digital noise reduction: | 3D DNR

## Compression Standard

Video Compression: | H.265/MJPEG

Video bit rate | 32Kbps~8Mbps

Triple Streams: | YES

## Image

Max. Image Resolution: | 3840x2160

Frame Rate: | 50 Hz: 25 fps (3840 x 2160)  
60 Hz: 30 fps (3840 x 2160)

Sub Stream: | 50 Hz: 25 fps(2540 x 1440)  
60 Hz: 30 fps(2540 x 1440)

## Network

Protocols: | Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception

Protocols: | TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP, NTP,UPnP,SMTP,IPv6,

General Function: | Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering

System Compatibility: | ONVIF (Profile S, Profile G),ISAPI

---

## General

---

Operating Conditions: | -30 °C ~ 60 °C (-22 °F ~ 140 °F)  
Humidity 95% or less (non-condensing)

---

Power Supply: | 12 VDC ± 25%

---

Weather Proof: | IP65

---

IR Range: | Up to 40m

---

Dimensions: | 225(W) x 76(H) x73(D)mm

---

Weight: | **1.4KG**

---