

## FT-10XMTH200S

### Camera

---

Image Sensor: | 2MP Progressive Scan CMOS

---

Effective Pixels: | 1920(H)x1080(V)

---

Signal System: | PAL/NTSC

---

White Balance: | Auto

---

AGC: | Auto/Manual

---

BLC: | Support

---

Focal Length: | 5.1-51MM, 10X

---

Signal Transfer: | AHD/CVI/TVI/CVBS Selectable

---

### Pan & Tilt

---

Rotation Range: | Pan:0°~160° , Tilt: -45°~25°Manual

---

Rotation Speed: | Pan:0~30°/s

---

Preset Points: | 220pcs preset( Dwell time 01-60s interval available)

---

Guard Tours: | 1 groups ( Each group 16 preset, dwell time and speed selectable)

---

AB scan range: | Any point in Pan range: 0°~160°

---

AB scan speed: | 1-9 grades

---

### Infrared

---

IR irradiation distance: | 100m

---

LEDs: | 35μx6PCS IR LEDS

---

Support Ambient Light  
Detection: | IR illumination on 1-9 Grads selectable

---

### General

---

RS-485 Protocols: | Pelco-P, Pelco-D

---

Menu Language: | English

---

Power Supply: | 12V DC

---

Power Consumption: | ≤10W

---

Lightning Protection: | Transient voltage 6000V

---

Working Temperature/H  
umidity: | -15°C~+60°C

---

Dimensions: | 26.5\*13.7\*13

---

Weight (approx.): | 3.5KG

---